

OK to ENTER EMF

Application No. 10/077,730

Docket No.: 83180US1

Amendment dated March 13, 2006

Reply to Office Action of June 1, 2005

AMENDMENTS TO THE CLAIMS

1. (currently amended) An automatic gain control radio frequency

(RF) signal processor, comprising:

an attenuator having an input for receiving an analog RF input signal, an output for applying an attenuated output signal, and a variable gain control input;

an amplifier having an input coupled to the attenuator output and an output;

a bandpass filter having an input coupled to the amplifier output and an output;

a single analog to digital (ADC) having an input coupled to the bandpass filter output and an output for providing a digitized ADC signal;

a digital logic circuit having an input for receiving the ADC signal, a first output coupled to the variable gain control input of said attenuator, and a second output, said digital logic circuit including signal detection logic for detecting the presence of a pulse within the ADC signal, determining a peak amplitude value of the pulse, and based on the peak

Application No. 10/077,730

Docket No.: 83180US1

Amendment dated March 13, 2006

Reply to Office Action of June 1, 2005

amplitude value generating an attenuation value at said first output that is applied to the variable gain control input of said attenuator; and

a first in [[first]] first out (FIFO) buffer having an input coupled to the second digital logic circuit output and an output for producing an attenuated, gain controlled, digitized output.

2. (previously presented) A processor as in claim 1, wherein the RF input signal is an intermediate frequency (IF) signal.

3. (original) A processor as in claim 1, wherein the signal detection logic comprises:

a threshold logic for detecting the presence of a pulse within the ADC signal; and

a control logic for generating said attenuation value and for controlling a flow of data into the FIFO.

Application No. 10/077,730

Docket No.: 83180US1

Amendment dated March 13, 2006

Reply to Office Action of June 1, 2005

4. (previously presented) A processor as in claim 3, wherein the RF input signal is an intermediate frequency (IF) signal.

5. (original) A processor as in claim 1, wherein the digital logic circuit further comprises a digital delay at said second digital logic circuit output.

6. (original) A processor as in claim 5, wherein the signal detection logic comprises:

a threshold logic for detecting the presence of a pulse within the ADC signal; and

a control logic for generating said attenuation value and for controlling a flow of data into the FIFO.

7. (original) A processor as in claim 6, wherein the RF input signal is an IF signal.

Application No. 10/077,730

Docket No.: 83180US1

Amendment dated March 13, 2006

Reply to Office Action of June 1, 2005

8. (original) A processor as in claim 1, wherein the signal detection logic includes storing a desired number of samples before the RF signal is detected and a desired number of samples after the RF signal is stored in the FIFO.

9. (original) A processor as in claim 1, wherein a final data sample associated with the RF signal includes a unique bit pattern recognized by the FIFO.

10-11 (canceled)

12. (currently amended) ~~A method as in claim 10, further comprising the step of~~ A method of processing an radio frequency (RF) input signal, comprising the steps of:

(a) receiving an RF signal;

(b) inputting the RF signal to an attenuator to produce an attenuator output;

Application No. 10/077,730

Docket No.: 83180US1

Amendment dated March 13, 2006

Reply to Office Action of June 1, 2005

- (c) applying the attenuator output to an amplifier while controlling a variable gain in the attenuator to produce a controlled amplified output;
- (d) passing the amplified output through a bandpass filter to produce a filtered RF output;
- (e) applying the filtered RF output to an analog to digital (ADC) to produce a digitized output signal;
- (f) applying the digitized output signal to a signal detection logic to determine an attenuation value and to produce a delayed output signal;
- (g) repeating steps (a) - (f) for each of a plurality of ADC data samples;
- (h) establishing a threshold for detecting the presence of a pulse within the plurality of ADC data samples;
- (i) applying the delayed output signal to a buffer to produce a buffered signal output;
- (j) controlling a flow of data into the buffer; and
- (k) applying the attenuation value to the attenuator to establish an updated attenuation gain value.

Application No. 10/077,730

Docket No.: 83180US1

Amendment dated March 13, 2006

Reply to Office Action of June 1, 2005

13. (currently amended) ~~A method as in claim 10, further comprising~~
the step of A method of processing an radio frequency (RF) input
signal, comprising the steps of:

(a) receiving an RF signal;

(b) inputting the RF signal to an attenuator to produce an attenuator
output;

(c) applying the attenuator output to an amplifier while controlling a
variable gain in the attenuator to produce a controlled amplified output;

(d) passing the amplified output through a bandpass filter to produce a
filtered RF output;

(e) applying the filtered RF output to an analog to digital (ADC) to
produce a digitized output signal;

(f) applying the digitized output signal to a signal detection logic to
determine an attenuation value and to produce a delayed output signal;

(g) repeating steps (a) - (f) for each of a plurality of ADC data
samples;

Application No. 10/077,730

Docket No.: 83180US1

Amendment dated March 13, 2006

Reply to Office Action of June 1, 2005

(h) establishing a threshold for detecting the presence of a pulse within the plurality of ADC data samples;

(i) averaging a number of data samples from the ADC to determine a moving average pulse amplitude;

(j) applying the delayed output signal to a buffer to produce a buffered signal output; and

(k) applying the attenuation value to the attenuator to establish an updated attenuation gain value;

14. (original) A method as in claim 13, further comprising the step of comparing the moving average pulse amplitude to a processing threshold value.

15. (original) A method as in claim 14, further comprising repeating for a number n samples the steps of averaging a number of data samples from the ADC and comparing the moving average pulse amplitude to a

Application No. 10/077,730

Docket No.: 83180US1

Amendment dated March 13, 2006

Reply to Office Action of June 1, 2005

processing threshold value to determine whether an assigned number m of the n averages are above the processing threshold value.

16. (original) A method as in claim 15, further comprising the step of signifying the end of the pulse when an assigned number i out of j averages are below the processing threshold value.

17. (original) A method as in claim 16, wherein the moving average is computed using four data samples.

18. (original) A method as in claim 16, wherein the end of pulse is signified when i of j averages are below a noise threshold value.

19-20. (canceled)

Application No. 10/077,730

Docket No.: 83180US1

Amendment dated March 13, 2006

Reply to Office Action of June 1, 2005

21. (currently amended) ~~A processor as in claim 20, wherein the signal~~

~~detection logic comprises~~ An automatic gain control radio frequency

(RF) signal processor, comprising:

an attenuator having an input for receiving an analog RF input
signal, an output for applying an attenuated output signal, and a variable
gain control input;

an amplifier having an input coupled to the attenuator output and
an output;

a bandpass filter having an input coupled to the amplifier output
and an output;

a single analog to digital (ADC) having an input coupled to the
bandpass filter output and an output for providing a digitized ADC signal;

a first in first out (FIFO) buffer having an input and an output for
producing an attenuated, gain control, digitized output; and

a digital logic circuit having an input for receiving the ADC signal, a first
output coupled to the variable gain control input of said attenuator, and a
second output coupled to the buffer input, said digital logic circuit including
signal detection logic, and said signal detection logic comprising:

Application No. 10/077,730

Docket No.: 83180US1

Amendment dated March 13, 2006

Reply to Office Action of June 1, 2005

a field programmable gate array including a threshold logic for detecting the presence of a pulse within the ADC signal; and

a control logic for determining a peak amplitude value of the pulse, and based on the peak amplitude value generating an attenuation value at said first output that is applied to the variable gain control input of said attenuator, said control logic further controlling a flow of data into the buffer.

22. (currently amended) ~~A processor as in claim 19, wherein~~ An automatic gain control radio frequency (RF) signal processor, comprising:

an attenuator having an input for receiving an analog RF input signal, an output for applying an attenuated output signal, and a variable gain control input;

an amplifier having an input coupled to the attenuator output and an output;

a bandpass filter having an input coupled to the amplifier output and an output;

Application No. 10/077,730

Docket No.: 83180US1

Amendment dated March 13, 2006

Reply to Office Action of June 1, 2005

a single analog to digital (ADC) having an input coupled to the bandpass filter output and an output for providing a digitized ADC signal;

a first in first out (FIFO) buffer having an input and an output for producing an attenuated, gain control, digitized output; and

a digital logic circuit having an input for receiving the ADC signal, a first output coupled to the variable gain control input of said attenuator, and a second output coupled to the buffer input, said digital logic circuit including signal detection logic, and said signal detection logic comprising:

a threshold logic for detecting the presence of a pulse within the ADC signal; and

a control logic for determining a peak amplitude value of the pulse, and based on the peak amplitude value generating an attenuation value at said first output that is applied to the variable gain control input of said attenuator, wherein the control logic utilizes stored peak amplitude values of one or more previously detected pulses in order to better predict the required attenuation value, said control logic further controlling a flow of data into the buffer.

Application No. 10/077,730

Docket No.: 83180US1

Amendment dated March 13, 2006

Reply to Office Action of June 1, 2005

23-25 (canceled)

26. (new) A processor as in claim 21, wherein the RF input signal is an
intermediate frequency (IF) signal.